



# RAVENOL ATF J2/S Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1211115

**Oil type:** Synthetic

**Recommendation:** Mitsubishi 4031610 ATF Fluid J3, Mitsubishi MZ313771 ATF Fluid J2, Nissan 999MP-MTJ00P Matic Fluid J, Nissan 999MP-MTS00P Matic Fluid S, Nissan KE908-99932 Matic Fluid J, Nissan KLE2300002 Matic Fluid J, Nissan KLE24 00002 Matic Fluid S, Renault Matic J6

**Application:** Passenger car



**RAVENOL ATF J2/S Fluid** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF J2/S Fluid** is specifically designed for all 5, 6 and 7-speed JATCO automatic transmissions.

**RAVENOL ATF J2/S Fluid** ensures maximum wear protection and smooth shifting in all conditions.

**RAVENOL ATF J2/S Fluid** is red colored.

1L | 1211115-001

4L | 1211115-004

10L | 1211115-010

20L | 1211115-020

20L | 1211115-B20

60L | 1211115-060

60L | 1211115-D60

208L | 1211115-208

208L | 1211115-D28

1000L | 1211115-700

## Application Note

**RAVENOL ATF J2/S Fluid** is designed specifically for use in JATCO automatic transmissions as follows; JF613E - Renault gearbox AJ0 Laguna, Scenic, Espace, Latitude; Nissan Qashqai transmission AJ0; Mitsubishi Outlander Transmission F6AJA and W6AJA; JR710E and JR711E - Infiniti FX50, EX37, NISSAN FAIR LADY Z, SKYLINE, FUGA.

## Characteristics

- Excellent lubricity even at low temperatures in winter
- High and stable viscosity index
- Very good oxidation stability
- Extensive protection against wear, corrosion and foaming
- High thermal and oxidative stability
- An excellent cooling capability

# Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	838,0	EN ISO 12185
Colour		rot	VISUELL
Pourpoint	°C	-51	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**

18.07.2023